

SUPERLOCK 2.0 DEADLOCK

Specification Sheet BD 2.0

FEATURES

- The single-body design removes joints and welds, increasing durability and giving the lock a clean, professional finish.
- Engineered and tested for high-impact outdoor use, the Superlock 2.0 range delivers unmatched strength, and reliability.
- Simple deadlocking action – the lock is opened and closed with a key.
- Easy to fit – Slim 70mm (2 3/4") wide lock case along with adjustable and removable latchbolt ensure easy fitting to gates.
- Latchbolt is adjustable in length for precise fitting on site.
- Universal for both left hand and right hand gates.
- Supplied with bolt support plate, gate post keep plate, and 3 keys.







PRODUCT DETAILS

Product code	Description
BD1030	To fit up to 30mm (1 1/4") box section
BD4060	To fit 40 to 60mm box section (1 1/2" to 2 1/4")



INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 140mm (5 1/2") centres for fixing bolts provided.
2. Drill a second 18mm (3/4") clearance hole for the deadbolt at 60mm (2 3/8") centres up from the bottom fixing hole.
3. Hold the lock against the back of the box section and screw the deadbolt through the middle hole.
4. Lock the deadbolt in place with the hex key supplied by inserting the hex key into the end of the deadbolt.
5. Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt moves freely.
6. Using the provided fixings, fix the keep plate by screw fixing onto the gate post.



MAINTENANCE

Every 6 months, lubricate the latchbolt with light oil.
Annually, dismantle the lock and spray mechanism with light oil.